




Translucent Building Elements

Lichtbauelemente



TRANSLUCENT BUILDING ELEMENTS



Translucent Building Elements



Multi Wall Sheets
Hohlkammerscheiben



Multi Function Panels
Multi - Funktions-Paneele



Translucent Building Elements

Advantages

- Polycarbonate is a crystal clear, high impact thermoplastic
- Temperature resistance from -40 to +115°C, temporarily up to 130°C
- Impact resistance virtually unchanged within these temperatures
- Good long term performance through UV protection
- 10 years warranty against yellowing - ageing - hail stone
- Translucent with excellent thermal properties

Applications

- Glazings
- Sports and industrial halls
- Roofing construction
- Northern Lights
- Window glazing
- Interior applications, e. g. partition walls or exhibition stand constructions
- Refurbishments for wall and roof
- Rain screens
- Curtain facades

Available thicknesses/ manufacturing program

40	Panel	Up-value W/m ² K**	Weight in kg/m ²	Building width (mm)
	2540-4	1.3 - 1.5 W/m ² K	approx. 4.0 kg/m ²	500 (+1/-1%)
	2540-4 MC	1.3 - 1.6 W/m ² K	approx. 4.0 kg/m ²	500 (+1/-1%)
	2540-6	1.1 - 1.2 W/m ² K	approx. 4.2 kg/m ²	500 (+1/-1%)
	2540-7	1.0 - 1.1 W/m ² K	approx. 4.3 kg/m ²	500 (+1/-1%)
	2540-10	1.0 W/m ² K	approx. 4.2 kg/m ²	500 (+1/-1%)

PC 2540-4

Colours:

Standard: crystal / opal / Bicolor*

*Upon request both sides UV-coextrusion possible

Color version: from 300 m²

Bicolor version: from 150 m²



PC 2540-4 MC

Colours:

Standard: crystal / opal

Color version: from 300 m²



PC 2540-6

Colours:

Standard: crystal / opal / color*

Color version: from 300 m²




PC 2540-7

Colours:

Standard: crystal / opal / Decocolor*

Color version: from 450 m²

Decocolor version: from 150 m²



PC 2540-10

Colours:

Standard: crystal / opal

Color version: from 300 m²





RT-Thermolight
RT-Thermolight

U-Panels
U-Paneele


Windows
Fenster

Do it yourself
Do it yourself

50	Panel	Up-value W/m ² K**	Weight per kg/m ²	Building width (mm)
	2550-10	0.80 - 0.92 W/m ² K	approx. 5.0 kg/m ²	495 (+1/-1%)

PC 2550-10

Colours:
Standard: crystal / opal / color*




Duicolor version: from 300 m²
Color version: from 300 m²

60	Panel	Up-value W/m ² K**	Weight per kg/m ²	Building width (mm)
	2560-12	0.71 - 0.77 W/m ² K	approx. 5.8 kg/m ²	500 (+1/-1%)

PC 2560-12

Colours:
Standard: crystal / opal



Color version: from 300 m²

Product versions

Color version: fully coloured panel



Bicolor version: colouring of the inner layer



Decocolor version: colouring of the outer layer



Duicolor version: colouring of approx. one half of the panel




* Minimum quantities, other colour combinations and our versatile product versions can be viewed in our technical manuals.






** Up-values

Depending on horizontal or vertical installation situation as interior or exterior application according to DIN EN ISO 6946:2008/ DIN EN ISO 10077-2:2008


Panels




40



50



60



Translucent Building Elements

Multi Wall Sheets
Hohlkammerscheiben

Multi Function Panels
Multi - Funktions-Paneele


Translucent Building Elements

Fastening / fixing

The fasteners slide into the panel groove and are fixed at the substructure. The fasteners provide a continuous and seamless glazing, which gives a light and smooth appearance to the façade.



Fastener

40



40

System	Clip fastener
PC 2540-x AF 50	49404050
PC 2540-x AF 100	494040100





50



50

System	Clip fastener
PC 2550-10 AF 60	49405060
PC 2550-10 AF 120	494050120





RT-Thermolight
RT-Thermolight

U-Panels
U-Paneele




Windows
Fenster

Do it yourself
Do it yourself

Material properties

The Rodeca clip fastener is made of extruded aluminium (EN AW 6060, status T66 according to DIN EN 755-2).


60	System	Clip fastener
	PC 2560-12 AF 60	49405060
	PC 2560-12 AF 120	494050120



Fastener




60



Translucent Building Elements

 Multi Wall Sheets
Hohlkammerscheiben

 Multi Function Panels
Multi - Funktions-Paneele

 Translucent Building Elements

Thermally broken aluminium frame profiles

The thermally broken perimeter frame profiles are made of extruded aluminium (type EN AW-6060, status T 66 according to DIN EN 755-2). The ribs are made of fibre glass reinforced polyamide PA 66 with fibre glass part of 25%. The gaskets are made of TPE.

Non-thermally broken aluminium frame profiles

The non-thermally broken perimeter frame profiles are made of extruded aluminium (type EN AW-6060, status T 66 according to DIN EN 755-2). The gaskets are made of TPE.

Framing systems

The perimeter frame profiles are available in thermally broken and non-thermally broken versions. They provide the main retention point of the panels to give a clean and water tight finish to the facade perimeter. Available in mill or anodized finish or powder coated to RAL.





RT-Thermolight
RT-Thermolight

U-Panels
U-Paneele



Windows
Fenster

Do it yourself
Do it yourself




Profiles


40



50




60



An example for thermally broken frame profiles

Two pieces aluminium frame profile with inner and outer gasket



Application

Installation advice, application requirements and further technical information can be viewed in our technical manuals and installation manuals.



Germany

RODECA GmbH
Freiherr-vom-Stein-Straße 165
D-45473 Mülheim an der Ruhr
Fon +49 (0) 208 76502-0
Fax +49 (0) 208 76502-11
info@rodeca.de
www.rodeca.de

United Kingdom

RODECA Ltd.
Bentalls House
Bentalls
Pipps Hill Industrial Estate
Basildon
Essex SS14 3BS
Fon + 44 (0) 1268 531466
Fax + 44 (0) 1268 526351
sales@rodeca.co.uk
www.rodeca.co.uk

Italy

ANSA Termoplastici S.r.l./RODECA Italy
Concessionaria per l'Italia di RODECA GmbH
Via Nazionale, 66
24060 Sovere (BG)
Fon +39 035 981431
Fax +39 035 981529
info@rodeca.it
www.rodeca.it

The Netherlands

RODECA Systems b.v.
Koperweg 11 N
2401 LH Alphen aan den Rijn
Fon +31 (0) 172 416 747
Fax +31 (0) 172 419 090
info@rodeca.nl
www.rodeca.nl

Belgium and Luxembourg

RODECA Systems BELUX bvba
Wupstraat 37
2812 Muizen/Mechelen
Mobile +32 (0) 468 137 677
Fax (NL) +31 (0) 172 419 090 (RODECA Systems b.v.)
info@rodeca.be
www.rodeca.be

South America

REPLAEX RESINAS PLÁSTICAS EXTRUDADAS LTDA
Autorizado America do Sul de RODECA GmbH
Estrada da Ligação, 839 - Taquara - Rio de Janeiro
RJ - BRASIL
cep. 22713-470
Fon : +55 (0) 21 2446-8811
Fax : +55 (0) 21 2446-7181
vendas@replaex.com.br
www.replaex.com.br

The RODECA product groups overview / Die RODECA Produktgruppen im Überblick:



Translucent Building Elements

Lichtbauelemente



Multi Wall Sheets

Hohlkammerscheiben



Multi Function Panels

Multi-Funktions-Paneele



U-Panels

U-Paneele



RT-Thermolight

RT-Thermolight



Windows

Fenster



Do it yourself

Do it yourself